



## Sales Specification

# Methyl Chloride (CH<sub>3</sub>Cl)

## Technical Grade

<u>COMPONENT</u>	<u>SPECIFICATIONS</u>
Methyl Chloride, wt%	99.95 min.
Dimethyl Ether, ppm	20 max.
Lower Boiling Compounds, ppm	250 max.
Higher Boiling Compounds, ppm	100 max.
Water, ppm	80 max.
Acidity, ppm as HCl	10 max.
Nonvolatile Residue, ppm	100 max.

### CONTAINERS:

Tank Cars (DOT 105J300W and DOT 112J340W) - 25,000 and 26,000 gallon

Tank Trucks (DOT MC-331) - Maximum weight load of approximately 42,000 pounds

Form#: 510 04/2011



**Occidental Chemical Corporation**  
A subsidiary of Occidental Petroleum Corporation

14555 Dallas Parkway, Suite 400  
Dallas, TX 75254  
800-752-5151

**Important: The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and Occidental Chemical Corporation assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.**