



Sales Specification

22° Bé Muriatic Acid (HCl)

Food Grade

<u>COMPONENT</u>	<u>SPECIFICATIONS</u>
Assay, °Baumé	22.0 min.
Hydrogen Chloride, wt. % as HCl	35.21 min.
Iron, ppm as Fe	3 max.
Sulfate, ppm as SO ₄	60 max.
Heavy Metals as Pb, ppm	1 max.
Arsenic, ppm as As	0.5 max.
Oxidizing Substances, ppm as Cl ₂	10 max.
Color, APHA	30 max.
Extractable Organic Compounds	
Total Organic Compounds (Non-Fluorine-Containing), ppm	5 max.
Fluorinated Organic Compounds, ppm	25 max.
*Residue on Ignition, ppm	80 max.

* According to test requirements appearing in the *National Formulary 38*

Meets Federal Specification O-H-765E (replaced by ASTM E1146-97)

Meets requirements of ASTM E1146-16

NSF Listed, NSF/ANSI Standard 60 (from Wichita, KS)

Meets current cGMP and Food Chemical Codex (FCC) requirements.

Produced in compliance with FDA FSMA Preventive Controls Rules for Human Food, September 17, 2015

Meets Global Food Safety Initiative - Produced at a SQF Certified Facility.

CONTAINERS:

Tank Cars - 20,000 gallon, rubber lined

Tank Trucks - 4,500 and 5,000 gallon, rubber lined

Form#: 122FG 08/2021



Occidental Chemical Corporation
A subsidiary of Occidental Petroleum Corporation

14555 Dallas Parkway, Suite 400
Dallas, TX 75254
800-752-5151

Important: The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and Occidental Chemical Corporation assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.